		Page: 1
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pyroil™ DOT 3 BRAKE FLUID


<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney)


GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Response:
Get medical advice/ attention if you feel unwell.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS


Substance / Mixture : Mixture
 Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
TRIETHYLENE GLYCOL MONOBUTYL ETHER	143-22-6	Eye Dam. 1; H318	>=30.00 - < 40.00
POLYOXYETHYLENE MONOBUTYL ETHER	9004-77-7	Eye Dam. 1; H318	>=20.00 - < 30.00
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	Eye Irrit. 2A; H319	>=5.00 - < 10.00
POLYETHYLENE GLYCOL	25322-68-3	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>=1.50 - < 5.00
TRISODIUM PHOSPHATE	7601-54-9	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335	>=1.50 - < 5.00
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	>=1.50 - < 5.00
DIISOPROPANOLAMINE	110-97-4	Eye Irrit. 2A; H319	>=1.50 - < 5.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.


		Page: 3
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
pain in the abdomen and lower back
Blurred vision
lung edema (fluid buildup in the lung tissue)
acute kidney failure (sudden slowing or stopping of urine production)
Difficulty in breathing
Diglycol ethers may cause acidosis.
Excessive levels of phosphorus can cause low blood calcium, with tetany and convulsions.
Diglycol ethers may cause acidosis.
Excessive levels of phosphorus can cause low blood calcium, with tetany and convulsions.
May cause damage to organs through prolonged or repeated exposure if swallowed.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local


		Page: 4
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

- circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Alcohols
Aldehydes
ethers
Ketones
Organic acids
Oxides of phosphorus
Sodium oxides
Nitrogen oxides (NOx)
- Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters


Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m ³	US WEEL
TRISODIUM PHOSPHATE	7601-54-9	STEL	5 mg/m ³	US WEEL
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	TWA	10 ppm Inhalable fraction and vapor	ACGIH
DIISOPROPANOLAMINE	110-97-4	TWA	10 ppm	SUPLR EXP
		TWA	10 ppm	SUPLR EXP

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection


Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : clear, yellow
- Odour : mild
- Odour Threshold : No data available
- pH : +/- 1.8 9.3
- Melting point/freezing point : -58 °F / -50 °C
- Boiling point/boiling range : 401 °F / 205 °C
(1013 hPa)
- Flash point : 275 °F / 135 °C
Method: Tag closed cup
- Evaporation rate : < 0.01
n-Butyl Acetate
- Flammability (solid, gas) : No data available
- Upper explosion limit : 36 %(V)
Calculated Explosive Limit
- Lower explosion limit : 0.9 %(V)
Calculated Explosive Limit
- Vapour pressure : 169.3164 hPa (25 °C)
Calculated Vapor Pressure
- Relative vapour density : 6AIR=1

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Relative density : 1.039 (20 °C)

Density : Average 1.035 g/cm3 (4 °C)

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY


Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : Avoid heat, open flame, and prolonged storage at elevated temperatures.
excessive heat
temperatures above 150 degrees F (66 °C)
Do not allow evaporation to dryness.
Exposure to moisture

Incompatible materials : Avoid contact with:
Acids
Alkaline earth metals
aluminum
Amines
Ammonia
Bases
Copper
galvanized metals
halogenated hydrocarbons

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

magnesium
 nitrites
 Organic materials
 Oxidizing agents
 Reducing agents
 strong alkalis
 Zinc

This product should not be used in conjunction with trimethylol propane or trimethylol propane-derived products. There is a possibility that bicyclic phosphates or phosphites can be produced as a result of the thermal decomposition of this product in combination with trimethylol propane, trimethylol propane-derived products or their corresponding trimethylol propane alkane homologs. Bicyclic phosphates and phosphites are a class of materials with acute neurotoxic properties which produce characteristic convulsive seizures in test animals.

Hazardous decomposition products

Alcohols
 Aldehydes
 carbon dioxide and carbon monoxide
 ethers
 Hydrocarbons
 Nitrogen oxides (NOx)
 Organic acids
 Oxides of phosphorus
 Sodium oxides
 ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion

Acute toxicity

Not classified based on available information.


Product:

Acute oral toxicity :

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity :

Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Components:

TRIETHYLENE GLYCOL MONOBUTYL ETHER:

Acute oral toxicity : LD50 (Rat): 5,300 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 3,502 mg/kg

POLYOXYETHYLENE MONOBUTYL ETHER:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): 3,540 mg/kg

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Acute oral toxicity : LD50 (Rat): 3,305 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 2,734 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 500 mg/kg
Application Route: Intraperitoneal

POLYETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Rat): > 14,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg


TRISODIUM PHOSPHATE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 0.83 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.

DIETHYLENE GLYCOL:

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

DIISOPROPANOLAMINE:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute oral toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 8,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

TRIETHYLENE GLYCOL MONOBUTYL ETHER:

Result: No skin irritation

POLYOXYETHYLENE MONOBUTYL ETHER:

Result: Slight, transient irritation

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Result: Slight, transient irritation

POLYETHYLENE GLYCOL:

Species: Rabbit

Result: No skin irritation

TRISODIUM PHOSPHATE:

Result: Irritating to skin.

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

DIISOPROPANOLAMINE:

Result: No skin irritation


Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation

Remarks: Expert judgement

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

TRIETHYLENE GLYCOL MONOBUTYL ETHER:

Result: Corrosive

POLYOXYETHYLENE MONOBUTYL ETHER:

Result: Corrosive

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Result: Severely irritating to eyes

POLYETHYLENE GLYCOL:

Species: Rabbit

Result: No eye irritation

TRISODIUM PHOSPHATE:

Result: Irritating to eyes.

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

DIISOPROPANOLAMINE:

Result: Severely irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

POLYOXYETHYLENE MONOBUTYL ETHER:

Test Type: Maximisation Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

POLYETHYLENE GLYCOL:


Species: Humans

Assessment: Does not cause skin sensitisation.

TRISODIUM PHOSPHATE:

Test Type: Local lymph node assay

Species: Mouse

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 429

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Result: In vivo tests did not show mutagenic effects

POLYETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

TRISODIUM PHOSPHATE:


Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
Remarks: Information given is based on data obtained from similar substances.

DIETHYLENE GLYCOL:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

: Test species: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Effects on fertility : Symptoms: No effects on fertility

STOT - single exposure

Not classified based on available information.

Components:

TRISODIUM PHOSPHATE:

Exposure routes: Inhalation

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Components:

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

DIETHYLENE GLYCOL MONOBUTYL ETHER:

NOAEL: 250 mg/kg

LOAEL: 1,000 mg/kg

Application Route: Oral

Target Organs: Blood

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

DIETHYLENE GLYCOL:

Liver

Further information

Product:

Remarks: No data available


Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

POLYOXYETHYLENE MONOBUTYL ETHER:

Toxicity to fish : LC50 (Flatfish, flounder (*Scophthalmus maximus*)): > 1,800 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Method: OECD Test Guideline 203

Toxicity to algae : ErC50 (*Skeletonema costatum* (marine diatom)): 391 mg/l
 Exposure time: 72 h

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Toxicity to fish : LC50 (*Bluegill* (*Lepomis macrochirus*)): 1,300 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test Type: static test


Toxicity to algae : EC50 (*Desmodesmus subspicatus* (green algae)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to bacteria : EC50 (Bacteria): > 100 mg/l
 Exposure time: 96 h
 Test Type: Static

POLYETHYLENE GLYCOL:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): > 20,000 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other : LC50 (*Daphnia magna* (Water flea)): estimated 1,000 mg/l

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

aquatic invertebrates Exposure time: 48 h
Remarks: QSAR

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)):
estimated 56 mg/l
End point: Growth inhibition
Exposure time: 72 h
Remarks: QSAR

TRISODIUM PHOSPHATE:
Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
Remarks: Information given is based on data obtained from
similar substances.


Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
Remarks: Information given is based on data obtained from
similar substances.

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
Remarks: Information given is based on data obtained from
similar substances.

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
Remarks: Information given is based on data obtained from
similar substances.

DIETHYLENE GLYCOL:
Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
aquatic invertebrates Exposure time: 24 h
Test Type: static test
Method: DIN 38412

DIISOPROPANOLAMINE:
Toxicity to fish : LC50 (Carassius auratus (goldfish)): 1,100 mg/l
Exposure time: 24 h
Test Type: static test

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Persistence and degradability

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Biodegradability : Biodegradation: 89 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301C
 Remarks: Readily biodegradable

POLYETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 75 %
 Exposure time: 28 d
 Remarks: QSAR

TRISODIUM PHOSPHATE:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
 Biodegradation: 70 - 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

DIETHYLENE GLYCOL MONOBUTYL ETHER:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1

POLYETHYLENE GLYCOL:

Partition coefficient: n-octanol/water : log Pow: 0.1

DIETHYLENE GLYCOL:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
 Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

DIISOPROPANOLAMINE:

Partition coefficient: n-octanol/water : log Pow: -0.82


No data available

Mobility in soil

No data available

Other adverse effects

No data available

		Page: 17
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods


U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

		Page: 18
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TRISODIUM PHOSPHATE	7601-54-9	5000	100002

SARA 304 Extremely Hazardous Substances Reportable Quantity


This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Specific target organ toxicity (single or repeated exposure)

California Prop 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

		Page: 19
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 07/12/2018

<p>NFPA:</p>  <p>Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: #0056b3; color: white;">HEALTH</td> <td style="text-align: center;">0*</td> </tr> <tr> <td style="background-color: #ff0000; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #ffff00;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

		Page: 20
SAFETY DATA SHEET		Revision Date: 07/12/2018
		Print Date: 9/10/2018
		SDS Number: R0197992
Pyroil™ DOT 3 BRAKE FLUID		Version: 1.4
PYBF32		

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment


STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

	Page: 21
SAFETY DATA SHEET	Revision Date: 07/12/2018
	Print Date: 9/10/2018
Pyroil™ DOT 3 BRAKE FLUID	SDS Number: R0197992
PYBF32	Version: 1.4

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System